




EPP insulation box



EPP loading carrier



XPS insulation boards



EPS parts with high density

Compactor Systems with Silo	Buffalo 60 Silo line	Buffalo 120 Silo line	Buffalo 250 Silo line	Buffalo 250x2 Silo line
Capacity ¹⁾	up to 50 kg/h	up to 100 kg/h	up to 200 kg/h	up to 400 kg/h
Achievable compaction with EPP ¹⁾ Achievable compaction with XPS, EPS ¹⁾	up to 400 kg/m ³ up to 400 kg/m ³	up to 400 kg/m ³ up to 400 kg/m ³	up to 400 kg/m ³ up to 400 kg/m ³	up to 400 kg/m ³ up to 400 kg/m ³
Processible material densities	up to 150 g/l	up to 150 g/l	up to 150 g/l	up to 150 g/l
Processible height of foamed part	up to 350 mm	up to 350 mm	up to 400 mm	up to 400 mm
Actual charging opening (W x D)	1.000 x 600 mm	1.200 x 600 mm	1.400 x 700 mm	1.400 x 700 mm
Block dimensions	210 x 210 mm	320 x 320 mm	400 x 400 mm	400 x 400 mm
Assembly dimensions (L x D x H) ²⁾	11.135 x 3855 x 4.000 mm	11.515 x 4121 x 4.000 mm	12.570 x 4255 x 5.000 mm	12.570 x 4255 x 6.000 mm
Machine weight ³⁾	approx. 3.200 kg	approx. 3.900 kg	approx. 5.000 kg	approx. 6.600 kg
Electrical connection	25,6 kW	44,2 kW	51,9 kW	83,4 kW
Supply voltage (EU)	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz
Marking	CE	CE	CE	CE

Remarks: Compactor system can be delivered with belt conveyor or stair landing / Silo available in customized size

