

EPE not cross linked foam packages




EPE not cross linked production waste



EPE cross linked production waste



EPP insulation box



XPS insulation boards



EPS parts with high density

EPP loading carrier

Compactor Systems with Pre-breaker	Buffalo 60	Buffalo 120	Buffalo 250	Buffalo 250x2
Capacity ¹⁾	up to 50 kg/h	up to 100 kg/h	up to 200 kg/h	up to 400 kg/h
Achievable compaction with EPP ¹⁾	up to 400 kg/m ³	up to 400 kg/m ³	up to 400 kg/m ³	up to 400 kg/m ³
Achievable compaction with EPE ¹⁾	up to 600 kg/m ³	up to 600 kg/m ³	up to 600 kg/m ³	up to 600 kg/m ³
Achievable compaction with XPS, EPS ¹⁾	up to 400 kg/m ³	up to 400 kg/m ³	up to 400 kg/m ³	up to 400 kg/m ³
Processible material densities	up to 150 g/l	up to 150 g/l	up to 150 g/l	up to 150 g/l
Processible height of foamed part	up to 350 mm	up to 350 mm	up to 400 mm	up to 400 mm
Actual charging opening (W x D)	1.000 x 600 mm	1.200 x 600 mm	1.400 x 700 mm	1.400 x 700 mm
Block dimensions	210 x 210 mm	320 x 320 mm	400 x 400 mm	400 x 400 mm
Assembly dimensions (L x D x H) ²⁾	5.286 x 1.573 x 2.769 mm	5.717 x 1.705 x 2.769 mm	6.422 x 1.805 x 2.599 mm	6.422 x 2.280 x 3.199 mm
Machine weight	approx. 1.800 kg	approx. 2.200 kg	approx. 2.800 kg	approx. 5.000 kg
Electrical connection	20,8 kW	39,4 kW	45,6 kW	77,1 kW
Supply voltage (EU)	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz
Marking	CE	CE	CE	CE