



# HSM V-Press 504



## HSM V-Press 504 vertical baling press

The entry-level model HSM V-Press 504 allows for the eco-nomical disposal of your packaging waste.

### Technical data

<b>Order number:</b>	6151151	<b>Loading aperture width x height:</b>	700 x 470 mm
<b>EAN</b>	4026631074421	<b>Bale length x Bale width x Bale height:</b>	700 x 500 x 600 mm
<b>Pressing power:</b>	40 kN	<b>Bale weight:</b>	60 kg
<b>Specific pressing power:</b>	11,2 N/cm <sup>2</sup>	<b>Width x Depth x Height:</b>	1020 x 812 x 1922 mm
<b>Driving power:</b>	1,1 kW	<b>Weight:</b>	290 kg
<b>Voltage / Frequency:</b>	230 V / 50 Hz	<b>Related product line:</b>	V-Press
<b>Cycle time when idling vacío:</b>	27 s	<b>Type of consumables:</b>	Strapping tape
<b>Volume throughput in idle operation (theor.):</b>	3,75 m <sup>3</sup> /h	<b>Press material:</b>	Plastic film, Mixed paper, Cardboard
<b>Loading height:</b>	661 mm		

### Product information



Bale removal and transport with discharge trolley



HSM TCS (Torsion Control System) for monitoring press ram movement



Modern microprocessor controller with membrane keypad and text display





### Compresses cardboard and film

Suitable for cardboard as well as film.



### Automatic start

Automatic start of the pressing process after closing the door.



### Optimized pressing

Massive press ram and extremely robust press plate guidance.



### Double door

To fill the press, the upper half of the doors is swung to the right.



### Bell-crank lever

Bell-crank lever for quick and safe opening of the door.



### Strapping

Manual bale strapping with continuous polyester tape.

