



EPS packages or
EPS production waste



EPS 6, AIRPOP, STYROFOAM®

Compactor System, Type	Mammut 15	Mammut 60	Mammut 120	Mammut 200
Capacity ¹⁾	up to 15 kg/h	up to 60 kg/h	up to 120 kg/h	up to 200 kg/h
Achievable compaction ¹⁾	up to 250 kg/m ³	up to 350 kg/m ³	up to 350 kg/m ³	up to 350 kg/m ³
Processible material densities	up to 30 g/l	up to 30 g/l	up to 30 g/l	up to 30 g/l
Processible height of foamed part	up to 300 mm	up to 350 mm	up to 400 mm	up to 400 mm
Actual charging opening (W x D)	700 x 360 mm	800 x 500 mm	1.000 x 600 mm	1.000 x 600 mm
Block dimensions	130 x 130 mm	210 x 210 mm	320 x 320 mm	400 x 400 mm
Assembly dimensions (L x D x H)	2.824 x 440 x 1.602 mm	2.856 x 600 x 1.700 mm	3.357 x 1.240 x 1.950 mm	3.687 x 1.240 x 1.950 mm
Machine weight	310 kg	600 kg	1.000 kg	1.300 kg
Electrical connection	1,5 kW	5,5 kW	11,0 kW	15,0 kW
Supply voltage (EU)	3 x 230 V 50 Hz 3 x 400 V 50 Hz	3 x 400 V 50 Hz	3 x 400 V 50 Hz	3 x 400 V 50 Hz
Supply voltage (USA)	3 x 230 V 60 Hz 3 x 480 V 60 Hz	3 x 480 V 60 Hz	3 x 480 V 60 Hz	3 x 480 V 60 Hz
Marking	CE	CE	CE	CE

