



EPS fish boxes



EPS 6, AIRPOP, STYROFOAM®

Compactor Systems with Pre-breaker	Mammut 15 B1200	Mammut 60 B1200	Mammut 120 B1200	Mammut 250 B1400	Mammut 250x2 B 1400
Capacity <sup>1)</sup>	<b>up to 15 kg/h</b>	<b>up to 60 kg/h</b>	<b>up to 120 kg/h</b>	<b>up to 250 kg/h</b>	<b>up to 500 kg/h</b>
Achievable compaction <sup>1)</sup>	up to 350 kg/m <sup>3</sup>	up to 350 kg/m <sup>3</sup>	up to 350 kg/m <sup>3</sup>	up to 350 kg/m <sup>3</sup>	up to 350 kg/m <sup>3</sup>
Processible material densities	up to 40 g/l	up to 40 g/l	up to 40 g/l	up to 40 g/l	up to 40 g/l
Processible height of foamed part	up to 350 mm	up to 350 mm	up to 350 mm	up to 350 mm	up to 350 mm
Actual charging opening (W x D)	1.200 x 600 mm	1.200 x 600 mm	1.200 x 600 mm	1.400 x 600 mm	1.400 x 900 mm
Block dimensions	210 x 210 mm	320 x 320 mm	400 x 400 mm	400 x 400 mm	400 x 400 mm
Assembly dimensions (L x D x H) <sup>2)</sup>	4.373 x 1.573 x 2.419 mm	5.753 x 1.705 x 2.419 mm	6.248 x 1.755 x 2.499 mm	6.358 x 1.755 x 2.499 mm	6.358 x 2.280 x 3.199 mm
Machine weight	approx. 1.350 kg	approx. 1.900 kg	approx. 2.150 kg	approx. 2.450 kg	approx. 4.800 kg
Electrical connection	13,9 kW	15,9 kW	23,6 kW	26,6 kW	53,1 kW
Supply voltage (EU)	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz	3 x 480 V / 60 Hz
Marking	CE	CE	CE	CE	CE

